OSHA Silica Rule Compliance Instructions

D0835, D5835, or D1835 5-Inch Dust Buddie

- Compliant with Table 1, Section (xii) handheld grinders for uses other than mortar removal.
- Table 1 requires a dust collector with 25 CFM per inch of grinding wheel diameter. Use a Dustless HEPA Wet+Dry (D1606, D1618, D1619), Wet+Dry (D1603) to collect the dust. A Dust Droid 300, or Dust Droid 600 may also be used.
- A HEPA vacuum or wet methods are required for housekeeping.
- Follow included instructions for installation. Use the included spacers to ensure the grinding wheel is between 1/8 and 1/4 inch from the bottom of the brushes to ensure optimal dust collection.
- Wear the personal protective equipment meeting the APF recommendation in Table 1. Always use eye and ear protection.

Task	Table 1 Compliant?	Objective Data	Objective Data	Minimum CFM	Recommended Dust Collector	Notes
		Required?	Available	required		
Dry grinding	Yes	No	N/A	25 OFM	Wet+Dry, H⊞A Wet+Dry,	Keep the Dust Buddie in contact with the
on flat surfaces				per inch	HEPA Wet+Dry Pro	work surface.
				of wheel	Dust Droid 300, Dust Droid	
				diameter	600	